

The test results within this specification have been taken from random samples during new production operations. No 3rd party testing has been performed so these results should be seen as a guide only.

Product Specification – Technical (SAMPLE TESTING)

PRODUCT NAME: STEPLIGHT RED CODE: 24013

GENERAL

	NEIVAL								
	PROPERTY		SPECIFICATION						
G1	Length	m	20.0						
G2	Width	m	1.8						
G3	Area	m²	36						
G4	Density	kg/m³	60 NOMINAL						
G5	Roll weight incl. packaging	kg	16.1 ± 2						
G6	Colour Foam		Various						
G7	Backing		Laminate of red colour						
G8	Packaging		Clear plastic						

TECHNICAL

	PROPERTY		REQ. PER AS4288 – 1999	TYPICAL RESULT	TEST METHOD
T1	Thickness mm	ì	± 12%	7.0 NOMINAL	AS 2111.1-1996

AIRSTEP STEPLIGHT RED foam underlay is made in Dandenong Australia from recycled polyurethane foam. The underlay is produced by crumbing and binding the foam into a cylindrical log. This log is then peeled and laminated into a continuous sheet. All edges are square trimmed and the underlay is to be free of holes and inclusions.

The packaging is a heat sealed polyethylene wrap and end sealed with a metal clip.

CONTROLLED DOCUMENT - SUBJECT TO REVISION Information contained in uncontrolled or photocopied material may be superseded without notice.

Doc No:	QS LIGHT RED (A.S.)	Originator:	J Ross	Date:	01/04/14	Q.A. Officer: J Ross
Issue No:	1	Approved:	P Verschaeren	Date:	01/04/14	Page 1 of 1