




# Classic Oak



**0300**  
**24235**



**0350**  
**24438**



**0500**  
**24234**

# Classic Oak

Rich and full of vibrant colour accents that life the mood. A realistic rendering of the beauty and versatility of oak.

## Technical Data

<b>Type:</b>	Vinyl Plank Flooring	<b>Colours:</b>	3
<b>Dimensions:</b>	1320mm x 196mm	<b>Country of Origin:</b>	Belgium
<b>Thickness:</b>	2.5mm	<b>Finish:</b>	Matte
<b>Wear Layer:</b>	0.55mm	<b>Surface:</b>	Rustic Wood Emboss (EMB 24)
<b>Units Per Box:</b>	14	<b>Profile:</b>	Micro Bevel
<b>m<sup>2</sup> per box:</b>	3.62	<b>Coating System:</b>	Protectonite®
<b>m<sup>2</sup> per pallet:</b>	202.72	<b>Installation Method:</b>	Direct Stick

## Performance

<b>Dimensional Stability:</b>	(EN ISO 23999) ≤0.05%	<b>Flammability:</b>	(EN ISO 9239) CRF 6.4kW/m2
<b>Classification:</b>	(EN ISO 10874) 23, 33, 42	<b>Smoke Value:</b>	(EN ISO 9239) 130% minutes
<b>Abrasion Rating:</b>	(EN 660-2) Group T	<b>Slip Resistance:</b>	(AS 4586) P2, R9
<b>Impact Sound Reduction:</b>	Please refer to Godfrey Hirst Acoustic Performance specification sheet	<b>Castor Chair:</b>	(EN ISO 4918) No Damage
<b>Light Fastness:</b>	(EN ISO 105-B02) ≥6	<b>Residual Indentation:</b>	(EN ISO 24343-1) Norm: ≤0.10mm, 0.03mm
<b>Light Reflectance Values:</b>	100 55152 -57   530 55236-35   750 55935-26   740 55960-16	<b>Warranty:</b>	25 Year Moduleo Limited Residential Warranty*

## Sustainability

<b>Product Transparency:</b>	Global Green Tag, GreenRate Level A certified
<b>Accreditation:</b>	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
<b>Global Green Tag:</b>	GreenRate Level A Certified
<b>Indoor Air Quality:</b>	Green Building Council Compliant for VOC emission rate limits

