

Polaris 1200





110 Pearl Oak



300 Tan Hardwood



510 Flax Oak



525 Silk Spotted Gum



Classic Blackbutt



555 Bright Spotted Gum



560 Hazel Blackbutt



Tawny Blackbutt



585 Brindle Spotted Gum



710 Silver Hardwood



Stony Blackbutt



Iron Spotted Gum



Polaris 1200

The versatile Polaris range takes the look, feel and design of natural timber floors and adds a few extra touches. It is durable, easy to maintain and water resistant ^. The exquisite colour range provides endless options for a variety of interiors, including Australian species designs for a traditional look without the maintenance. Available in two sizes, Polaris 1200 is a shorter plank. All colours in this range are also available in the longer and thicker Polaris 1500 range.

Direct stick vinyl plank for a professional looking installation

Technical Data

Type:	Vinyl Plank Flooring
Dimensions:	1219mm x 228mm
Total Product Thickness:	3mm
Wear Layer:	0.3mm
Units Per Box:	12
m² per box:	3.35
m² per pallet:	187.6

Colours:	12
Finish:	Matte
Surface:	Embossed
Profile:	Square Edge
Coating System:	PUR
Installation Method:	Direct Stick

Performance

Dimensional Stability:	(ISO 23999) Length: 0.15%, Width: 0.05%, Curling 0.00%	L R
Thermal Conductivity:	TBA	V
Abrasion Rating:	(EN 660-2) Group T	F S
Impact Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet	
Light Fastness:	(EN ISO 105-B02) 6-7	S

110 - 31.89 | 300 - 20.07 | 510 - 28.06 | ight 525 - 20.60 | 545 - 13.37 | 555 - 13.70 | 560 - 18.15 | 570 - 9.60 | 585 - 8.64 | 710 Reflectance /alues: 29.61 | 735 - 14.38 | 790 - 10.41 Flammability: (EN ISO 9239) CRF 10.0kW/m2 Smoke Value: Direct Stick: (EN ISO 9239) 132% minutes I With Underlay: (ÉN ISO 9239) 184% minutes Slip Resistance: (AS 4586) P2, R9 Warranty: 15 Year Vinyl Plank Limited Residential

Warranty'

Sustainability

Product Transparency:	Global GreenTag, GreenRate Level A certified,Best Environmental Practice PVC certified product
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits



Water Resistant Surface[^]



Global GreenTag 0.3mm Wear layer GreenRate Level



Matte Finish



ISO 9001 Quality Management System



ISO 14001 Environment Management



Embossed



Square Edge



Plank I imited Residential Warranty











Polaris 1200

Affordable

Colour Variation

Best Environmental Practice PVC

